




Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349.Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



Туре

- 4 Stroke
- Air Cooled
- V Twin
- Overhead valve
- Vertical Shaft

Technical Specifications

 Engine Type 	4-Stroke, Vertical Shaft, V-Twin, OHV, Air-cooled,
 Number of cylinders 	2
 Bore x stroke 	73 x 72 mm
 Displacement 	603cm ³
 Max. power 	10.1 kW (13.5 hp) / 3600 rpm
 Max. torque 	37.0 Nm (27.3 ft.lbs) / 2000 rpm
 Fuel tank capacity 	
 Oil capacity 	2.0 litres
 Dry weight 	40.7 Kg
 Dimensions (L x W x H) (mm) 	468 x 429 x 544



Features

- 90 degree V-twin
- Automatic compression release
- Cast iron cylinder liners
- Clean out ports
- Electronic spark ignition
- Heavy duty shift type starter
- High performance lubrication system

- Internally vented carburetor with fuel shut-off solenoid
- Metal engine cover
- Overhead V-valves
- Rotating grass screen
- Single stage canister air filter
- Spherical combustion chambers

Options

- Muffler
- Oil pressure switches
- Shaft variations

- 20 Amp charge coil
- Various oil drains
- Various speed control system



FX Series FX481V

